








Item description	Qty.	Sample image
Concealed cup hinge 110°	2	
Concealed cup hinge mounting plate	2	
Dowel wood 8 x 30 mm	49	
Connector housing without rim for excenter connector 15 mm diameter for 19mm panel thickness	4	
Connector housing with rim for excenter connector 15 mm diameter for 16mm panel thickness	24	
Connecting bolt for excenter for 5 mm drill hole, drilling dimension B = 34 mm, bolt length = 35 mm	28	
Shelf support Ø 5mm x 16,5mm	2	
(optional for mounting bracket on sliding table saw) Screws DIN EN ISO 4017 M10 x 200 Or threaded rods 200mm	4	

# Fittings and materials list productionRack Cutting

---

(optional for mounting bracket on sliding table saw) Nut DIN EN ISO 4032 M10	4	
(optional for mounting bracket on sliding table saw) Washer DIN EN ISO 7089 Size Ø 10mm	8	

<b>Panel material</b>	<b>Qty. (incl. 30% waste)</b>
Chipboard-16mm_White	1,02 m <sup>2</sup>
Chipboard-19mm_Black	0,11 m <sup>2</sup>
Plywood-18mm	0,37 m <sup>2</sup>

<b>Edgeband material</b>	<b>Qty.</b>
ABS 23x2mm white	11,00 lfm
ABS 23x2mm black	2,09 lfm